

SUBMERSIBLE CENTRIFUGAL PUMPS

PERFORMANCE & SPECIFICATIONS

The PortaPump® Submersible, Battery-Powered Pump operates using any 12-volt car or truck battery. It comes equipped with cables and battery clips. Extremely portable, the pump weighs only 33 pounds (15 kg) and can fit through openings as small as 10" (25cm). Electrically safe and whisper quiet.



SPA1 1/2-E Metallic Performance



MAX FLOW


• 43 GPM (163 LPM)

PORTING

• NPT / BSP

WET END

• Aluminum



The SludgeMaster™ Submersible, Air-Powered Trash Pump handles mud, leaves, twigs, sand, sludge, trash-laden water and soft solids to 1 1/2" (3.8cm). High capacity, low head. The pump weighs only 59 pounds (26kg), and can fit through an opening as small as 14" (35cm). Sturdy construction for rough handling and long life. Optional rock screen available.



SMA3 Metallic Performance



MAX FLOW

• 300 GPM (1140 LPM)

PORTING



• NPT / BSP

AIR END

• Aluminum

WET END

• Aluminum



SCAN TO LEARN MORE
SANDPIPERPUMP.COM/SUBMERSIBLE

SPECIFICATIONS

PUMP MODELS	A	B	C	D	E	Connection Style	Pipe Size	Max Flow Per Minute	Max Solids Handling	Max Discharge Height
	Height	Width	Depth	Base to Center Discharge	Weight					
	inches (mm)	inches (mm)	inches (mm)	inches (mm)	Pounds (kg)					
SPA1 1/2-E	22 (560)	8.88 (225)	6.19 (157)	4.71 (119)	33 (15)	1 1/2" NPT	1.5 (38)	43 (163)	.06 (1)	25 (7.6)
SMA3	23.51 (597)	13 (330)	9 (229)	7.11 (180)	59 (26)	3" NPT	3 (75)	300 (1140)	1.5 (40)	65 (19.8)

Dimensional Tolerance: ±1/8" (± 3mm) • See service manual for complete specifications